



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G07F 7/10	A1	(11) International Publication Number: WO 99/62036
		(43) International Publication Date: 2 December 1999 (02.12.99)

(21) International Application Number: PCT/EP99/03429

(22) International Filing Date: 19 May 1999 (19.05.99)

(30) Priority Data:
981165 26 May 1998 (26.05.98) FI

(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON
(publ) [SE/SE]; S-126 25 Stockholm (SE).

(72) Inventor: ARKKO, Jari; Kauppalaantie 25 A 7, FIN-02700
Kauniainen (FI).

(74) Agent: BORENIUS & CO. OY AB; Kansakoulukuja 3,
FIN-00100 Helsinki (FI).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD AND APPARATUS FOR CHARGING IN A COMMUNICATIONS NETWORK

(57) Abstract

A user terminal (1) is connected to the Internet (7) through a telephone network (3, 4, 5) and a Network Access Server (6) operated by an Internet Service Provider (ISP). A protocol converter (8) exists between the telephone network (3, 4, 5) and the Network Access Server (6), and the converter (8) and Network Access Server (6) are coupled through a telecommunication link (9). User data is sent between the converter (8) and the Network Access Server (6) using a circuit switched protocol. Charging data is sent to the converter (8) from a RADIUS server (11) operated by the ISP using Internet Protocol (IP). In response to receipt of this charging data, charging messages are sent from the converter (8) to a billing system (3) of the telecommunications network. On the basis of these messages, the operator of the telecommunications network is able to bill the user for the used ISP services.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND APPARATUS FOR CHARGING IN A COMMUNICATIONS
NETWORK

Field of the Invention

5

The present invention relates to a method and apparatus for charging in a communications network. More particularly, though not necessarily, the invention relates to the provision of charging information to a
10 telecommunications operator from a data network accessible to a subscriber of the telecommunications operator.

Background to the Invention

15

The conventional way for a home user of a personal computer (PC) to access the Internet is to set up a telephone call, via his telephone operator which provides a modem pool, to an Internet Service Provider
20 (ISP). The access point for the user to the ISP is termed a Network Access Server (NAS). The NAS allocates an Internet Protocol (IP) address to the user PC for the duration of the connection and also acts as a protocol converter, converting the circuit switched data
25 transmissions of the telephone network into IP packet switched transmissions and vice versa. A typical ISP may provide many NASs spread over the geographical area in which the ISP operates.

30 In order to collect billing information and to verify user access rights, the ISP may have a small number of so-called "RADIUS servers" also spread over its coverage area. One RADIUS server may serve a few tens of NASs. Communication between the RADIUS servers and the NASs is
35 carried out using the secure RADIUS protocol (RADIUS stands for Remote Authentication Dial-In User Service

and is defined in IETF standards RFC 2138/2139) A user, who is a subscriber of the ISP, may then be billed for accessing the Internet on the basis of the information collected by the RADIUS server(s).

5

The Internet access system described above requires that the user has an agreement with the ISP, such that the ISP has information required for charging such as the user's name, address, telephone number etc. This will obviously restrict the number of different ISPs which the user may use.

10

Summary of the Invention

It is an object of the invention to overcome or at least mitigate the disadvantages of known data network access charging systems. In particular it is an object of the present invention to provide for the combining of telephone and data network charging such that a user may be provided with a single bill for both services.

20

According to a first aspect of the present invention there is provided a method of charging in a communication network in which a user terminal is connected to a data network through a telecommunications network and a Network Access Server, and in which a protocol converter exists between the telecommunications network and the Network Access Server, and the converter and the Network Access Server are coupled through a telecommunication link, the method comprising:

30

sending user data between said converter and the Network Access Server, via said telecommunication link, using a circuit switched protocol;

35

sending charging data from the data network to said converter using a packet switched protocol; and

in response to receipt of said charging data at said converter, sending from the converter to a billing

system of the telecommunications network charging messages on the basis of which the operator of the telecommunications network can bill the user.

5 Embodiments of the present invention provide a relatively straightforward means by which ISP charging information may be "repatriated" to a user's home telecommunications network. Thus, it is no longer necessary for a user to subscribe directly to an
10 individual ISP, only that the home telecommunications network has an appropriate re-charging agreement with the ISP. As it is possible to incorporate ISP charges into a bill generated by the telecommunications network, it is possible to levy relatively small charges for ISP
15 services.

Preferably, said data network comprises the Internet, and said converter between the telecommunications network and the Network Access Server also comprises an
20 Internet link in addition to said telecommunication link. This allows said charging data to be sent to the converter using Internet Protocol.

More preferably, said data network comprises a Web
25 server arranged in use to store information which is accessible to the user via the telecommunication network and the data network. The data network also comprises one or more charging servers arranged to record user access to the Web servers. Communication between the
30 Web servers and the charging servers may be done using a secure protocol, e.g. RADIUS. Either the web servers, or the charging servers, may be the source of said charging data sent to said converter.

35 In a preferred embodiment of the present invention, said converter converts Signaling System 7 (SS7) and T.1/E.1

protocol transmissions in the telecommunication network -
to the Integrated Services Digital Network (ISDN) for
transmission to the network access server over said
telecommunication link and vice versa. Said converter
5 also converts said charging data received from the data
network in IP into SS7 protocol charging messages (CRG
messages).

Alternatively, the data network may be a Local Area
10 Network (LAN) or a Wide Area Network (WAN).

According to a second aspect of the present invention
there is provided apparatus for charging in a
communication network in which a user terminal is
15 connected to a data network through a telecommunications
network and a Network Access Server, the apparatus
comprising:

a protocol converter for placing between the
telecommunications network and the Network Access
20 Server, where the converter and the Network Access
Server are coupled through a telecommunication link and
are arranged to send user data, via said
telecommunication link, using a circuit switched
protocol; and

25 charging data generating means for connection to
the data network and arranged to send charging data to
said converter using a packet switched protocol,

the protocol converter being further arranged, in
response to receipt of said charging data at said
30 converter, to send to a billing system of the
telecommunications network charging messages on the
basis of which the operator of the telecommunications
network can bill the user.

35 Preferably, said protocol converter provides a
T.1/E.1:SS7-to-PRI protocol converter between the

telecommunications network and said telecommunication link, and a IP-to-SS7 protocol converter between the telecommunications network and an IP link coupling the converter to the data network. More preferably, the
5 protocol converter is a physically discrete unit which is connected in use between an exchange of the telecommunications network and said telecommunication and IP links.

10 Brief Description of the Drawings

For a better understanding of the present invention and in order to show how the same may be carried into effect reference will now be made, by way of example, to the
15 accompanying drawings, in which:

Figure 1 shows schematically a communications system embodying the present invention; and

Figure 2 shows a flow diagram illustrating the method of operation of the system of Figure 1.

20

Detailed Description of Embodiments

In the schematic diagram of Figure 1, a PC 1 belonging to a user is connected via a modem of the PC 1 to a
25 subscriber telephone line 2 belonging to a public telephone network. The line 2 connects to an exchange 3 of the network and carries signals according to the Integrated Services Digital Network (ISDN) protocol. This protocol provides the user with two traffic
30 channels (B-channels) and one signalling channel (D-channel).

The exchange 3 is coupled to other telephone exchanges including those belonging to the same network and
35 exchanges belonging to other networks. In order to reach a final destination, a call from the user PC 1 may be routed via several exchanges including the local

exchange 3. Calls between the local exchange 3 are transmitted on 64Kbit/sec channels using E.1 protocol (a Time Division Multiple Access (TDMA) based protocol). Each channel is sub-divided into frames consisting of 31 segments and a single call from the user PC 1 may be allocated 1 segment per frame. As an alternative to the European E.1 protocol, the American T.1 protocol may be used.

10 A call between the local exchange and some other
exchange 4 is set-up using a signalling protocol known
as the Signalling System 7 protocol (indicated by
reference numeral 5 in Figure 1). This protocol is
defined by the ITU standards Q.761 to Q.764 and is
15 carried by a channel made up of 1 segment per TDMA
frame.

As has already been described above, in order for a subscriber to a public telephone network to access the Internet, a call must first be set-up between the subscriber's PC 1 and a Network Access Server of an Internet Service Provider. In Figure 1, such a Network Access Server is indicated by the reference numeral 6 and the Internet is indicated by numeral 7. Logging on to the Network Access Server 6 requires a call to be made from the user PC 1 to a telephone number (B-number) allocated by the telephone network to the Network Access Server 6. The call is routed through the local exchange 3 to the exchange 4 closest to the Network Access Server 6 using the SS7 signalling protocol as described above. The call is then routed through a converter unit 8 to a telephone line 9 connected to the Network Access Server 6 where access to the user PC 1 is granted on the basis of the subscriber number (A-number) transmitted as part of the call set-up procedure. Alternatively, access may be granted on the basis of a username and password entered by the subscriber.

In order to provide sufficient capacity to cope with a number of simultaneous Internet access requests, the telephone line 9 carries ISDN protocol signals according to the Primary Rate Interface (PRI), providing 30 B traffic channels and 1 D signalling channel. The Converter unit 8 therefore acts as an E.1/SS7-to-PRI protocol converter and vice versa.

Figure 1 shows two Web servers 10 on which are stored Web pages and other information accessible to a user via the Internet 7. It will be appreciated that a large number of Network Access Servers and Web servers will be separately coupled to the Internet 7.

In addition to controlling the Network Access Server 6, and possibly a number of Web servers 10, the ISP also has control of a RADIUS server 11. The RADIUS server 11 is so-called because it communicates with the Web servers 10 using a secure communication protocol known as RADIUS (although any other suitable Authentication-Authorisation-Accounting (AAA) protocol may be used)). The RADIUS server 11 acts as a billing co-ordinator for the Network Access Server 6 and a group of Web servers 10. More particularly, the RADIUS Server 11 receives caller identity information from the Network Access Server 6 (more particularly the access port ID of the subscriber into the Network Access Server and possibly the subscriber's A-number) together with call start and stop times. The RADIUS Server 11 also receives from the Web Servers 10 charging information relating to specific services provided by the Web servers 10 to the user. These services may include accessing premium rate services such as Web pages giving up-to-the-minute sports and business information, or accessing Web servers 10 located in a foreign country.

In order to allow the user to be billed on the basis of the information collected by the RADIUS server 11, the RADIUS Server 11 sends charging data to the converter unit 8 via an Internet link 12. The Converter unit 8 is for this purpose allocated an IP address and the link 12 uses the well known IP protocol. The IP address is sent to the RADIUS server 11 by the Network Access Server 6 during the initial connection phase. The protocol stack in this link comprises RADIUS over UDP over IP.

Upon receipt of the charging data from the RADIUS server 11, the converter unit 8 generates charging messages which are transmitted via the exchange 4 to the subscriber's local exchange 3 (or to some other billing coordinator of the public telephone network). The charging messages are in fact CRG messages as defined in SS7 standard Q.762 (although for example conventional charging "pulses" may be used instead). In addition to providing a E.1:SS7-to-PRI protocol converter, the converter unit 8 therefore also provides an IP-to-SS7 protocol converter.

It will be appreciated by the person of skill in the art that various modifications may be made to the above described embodiment without departing from the scope of the present invention. For example, charging data may be sent directly from the Web servers 10 to the converter unit via the Internet link 12, rather than through the RADIUS server 11. An Internet Service Provider may also utilise a number of different RADIUS Servers, each serving a particular group of Network Access Servers and/or Web servers.

It will also be appreciated that whilst the embodiment described above considers the Web servers, RADIUS

servers, and Network Access Server to be connected together via the Internet, this need not be so. The connections may be made via some other data communication links, e.g. lines leased by the ISP from a telecommunications network or a LAN or WAN owned by the
5 ISP. Similarly, the link between the RADIUS server 11 and the converter 8 may be made via a data link which does not form part of the open Internet network.

Claims

1. A method of charging in a communication network in which a user terminal is connected to a data network
5 through a telecommunications network and a Network Access Server, and in which a protocol converter exists between the telecommunications network and the Network Access Server, and the converter and the Network Access Server are coupled through a telecommunication link, the
10 method comprising:
 sending user data between said converter and the Network Access Server, via said telecommunication link, using a circuit switched protocol;
 sending charging data from the data network to said
15 converter using a packet switched protocol; and
 in response to receipt of said charging data at said converter, sending from the converter to a billing system of the telecommunications network charging messages on the basis of which the operator of the
20 telecommunications network can bill the user.
2. A method according to claim 1, wherein said data network comprises the Internet, and said converter between the telecommunications network and the Network
25 Access Server comprises an Internet link in addition to said telecommunication link, whereby said charging data is sent to said converter using Internet Protocol.
3. A method according to claim 2, wherein said data
30 network comprises a Web server arranged in use to store information which is accessible to the user via the telecommunication network and the Internet.
4. A method according to claim 3, wherein the data
35 network comprises one or more charging servers arranged to record user access to the Web servers.

5. A method according to claim 4, wherein communications between the Web servers and the charging servers are done using a secure protocol.

5

6. A method according to claim 4 or 5, wherein either the web servers, or the charging servers, are the source of said charging data sent to said converter.

10 7. A method according to any one of the preceding claims, wherein said converter converts Signaling System 7 (SS7) and T.1/E.1 protocol transmissions in the telecommunication network to the Integrated Services Digital Network (ISDN) for transmission to the Network
15 Access Server over said telecommunication link and vice versa.

8. A method according to claim 7 when appended to claim 2, wherein said converter converts said charging
20 data received from the data network in IP into SS7 protocol charging messages (CRG messages).

9. Apparatus for charging in a communication network in which a user terminal (1) is connected to a data
25 network (7) through a telecommunications network (3,4,5) and a Network Access Server (6), the apparatus comprising:

a protocol converter (8) for placing between the telecommunications network (3,4,5) and the Network
30 Access Server (6), where the converter (8) and the Network Access Server (6) are coupled through a telecommunication link (9) and are arranged to send user data, via said telecommunication link (9), using a circuit switched protocol; and


35 charging data generating means (11) for connection to the data network (7) and arranged to send charging

data to said converter (8) using a packet switched protocol,

the protocol converter (8) being further arranged, in response to receipt of said charging data at said converter (8), to send to a billing system (3) of the telecommunications network charging messages on the basis of which the operator of the telecommunications network can bill the user.

10 10. Apparatus according to claim 9, wherein said protocol converter (8) provides a T.1/E.1/SS7-to-PRI protocol converter between the telecommunications network (3,4,5) and said telecommunication link (9), and a TCP/IP-to-SS7 protocol converter between the
15 telecommunications network (3,4,5) and an IP link (12) coupling the converter (8) to the data network (7).

11. Apparatus according to claim 9, wherein the protocol converter (8) is a physically discrete unit
20 which is connected in use between an exchange (4) of the telecommunications network (3,4,5) and said telecommunication and IP links (9,12).

Fig. 1

2/2




Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03429

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G07F7/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G07F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	WO 99 08242 A (BRITISH TELECOMMUNICATIONS) 18 February 1999 (1999-02-18) page 4, line 13 - line 18 page 5, line 22 - page 6, line 29; figures ---	1-11
P, A	EP 0 848 361 A (NIXU) 17 June 1998 (1998-06-17) column 6, line 26 - line 38 column 10, line 22 - line 45 column 13, line 41 - line 48 abstract; figures 3-8 ---	1-11
A	EP 0 765 068 A (AT&T) 26 March 1997 (1997-03-26) column 6, line 39 - column 7, line 56; figures 1-4 --- -/--	1-11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

20 September 1999

Date of mailing of the international search report

29/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Neville, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/03429

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96 37848 A (WALKER ASSET MANAGEMENT) 28 November 1996 (1996-11-28) page 13 page 15, line 22 -page 16, line 36; figures ---	1-11
A	WO 97 03410 A (EGENDORF) 30 January 1997 (1997-01-30) page 3, line 11 - line 17 page 6, line 11 -page 7, line 3 page 9, line 1 -page 10, line 2; figures ---	1-11
A	WO 97 19414 A (OXFORD MEDIA PROPRIETY) 29 May 1997 (1997-05-29) page 3, line 37 -page 5, line 4 page 12, line 3 - line 31 ---	1-11
A	WO 97 01920 A (TELECOM FINLAND) 16 January 1997 (1997-01-16) abstract; figures -----	1-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC./EP 99/03429

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9908242 A	18-02-1999	AU 8637198 A	01-03-1999
EP 848361 A	17-06-1998	AU 5224698 A	03-07-1998
		EP 0917327 A	19-05-1999
		WO 9826381 A	18-06-1998
		NO 992776 A	13-08-1999
EP 765068 A	26-03-1997	US 5745556 A	28-04-1998
		AU 6571896 A	27-03-1997
		CA 2182818 A	23-03-1997
		JP 9153964 A	10-06-1997
		US 5864610 A	26-01-1999
WO 9637848 A	28-11-1996	AU 5922996 A	11-12-1996
		BR 9606368 A	23-12-1997
		CA 2195968 A	28-11-1996
		EP 0782728 A	09-07-1997
		JP 10507053 T	07-07-1998
		US 5737414 A	07-04-1998
WO 9703410 A	30-01-1997	US 5794221 A	11-08-1998
		AU 5986596 A	10-02-1997
		CA 2226253 A	30-01-1997
		EP 0845125 A	03-06-1998
WO 9719414 A	29-05-1997	AU 7556596 A	11-06-1997
WO 9701920 A	16-01-1997	FI 953208 A	29-12-1996
		EP 0872117 A	21-10-1998

